

Technical data

700B/C 'Marmiton'

Model:

Brick version : 700B

Refractory concrete ovenarch : 700C

Materials:

Refractory brick

Refractory concrete


Reinforced with metal fibres

Parts:

The hearthstone : 2 Parts

The oven arch : 1 Part

The arch



Characteristics:

Cooking chamber : 0.37 m²

Weight : 230 kg

Power used: Example with Beech (20 % humidity)

Pre-firing 1.15 Hour: 5.6 kg Wood/H (0.013 stere) = 22 kW/Hour

Cooking with the door opened : 2,3 kg Wood/H (0.05 stere/h) = 1.9 kW/Hour

Power going through the sides with the advised insulation : 0.4 KW/Hour

Radiation power (through the door) : 1.9 KW/Hour

Fresh air consumption : 132 m³/Hour at 20 °C

Minimal smoke pipe : Height 3 m- Part 190 cm²-Diameter 160 mm




Flue connector in conformity with standard LN1856-2

SMOKE TEMPERATURE

For oven stoves : 175°C

Maximum temperature for the use of the oven :

500°C



Equipment:

insulation door AC1R

External door AC6

Asher AC2

Flue connector AC101 or AC101SC

Vault thermometer AC20

Oven cover AC102



wood-fired oven 2017